

HARDWARE SPECIFICATION – DOUBLE DOORS

Pairs of doors may have Plain or Rebated meeting stiles. If the doors have rebated meeting stiles a rebate kit will be required for the lock or latch. Generally one of the doors in a pair is held in place with a pair of bolts – this door is known as the inactive leaf. The other, the working door, is the active leaf and is fitted with mortice lack or latch. For a balanced appearance we recommend dressing both doors with lever handles or pull handles.



Doors with rebated meeting stiles require a rebate kit for any mortice lock or latch that is fitted. Rebate kits are available to suit 13, 19 or 25mm rebates.

size



Lever action flush bolts may be fitted at the top and bottom of the inactive leaf. They may be fitted in the leading edge or the face of the door. Lever action flush bolts are available in the following sizes :

19 x 152mm	19 x 203mm
19 x 254mm	19 x 305mm
19 x 457mm	19 x 609mm
19 x 762mm	19 x 914mm

The top flush bolt should be of a suitable length to ensure the lever can be reached. The approximate length of the bolt should equal the door height minus 1800mm.

DOOR HEIGHT – 1800mm = APPROX BOLT LENGTH



DOOR FURNITURE RECOMMENDATIONS

We recommend matching furniture is fitted to the inactive leaf to achieve a balanced appearance.

The Active Leaf will be fitted with the mortice lock or latch. The Inactive Leaf will be fitted with the bolts to hold it in place.

Active Leaf :	Inactive Leaf :
Working set of lever handles / door knobs	Fixed dead set of lever handles / door knobs
OR	OR
Back to back set of pull handles	Back to back set of pull handles
OR	OR
Bolt fix pull handle with push plate	Bolt fix pull handle with push plate